

SI CAM

Aplique circular para montaje en techo o pared.

Cuerpo: polipropileno estabilizado frente al UV.

Difusor: policarbonato opal.

Acabado superficial: blanco o negro. Otros colores, consultar.

Distribución de la luz: simétrica.

Fuente de luz: LED.

Índice de reproducción cromática (CRI): CRI>80.

Temperatura de color (K): 3000K, 4000K.

Tolerancia de color (SDCM): 3 elipses de MacAdam.

Equipo de alimentación: On-Off (HF).

Bajo pedido: sensor de movimiento.

Grado de protección (IP): IP44.

Montaje: instalación directamente a techo o a pared mediante tornillos.

Áreas de aplicación: terrazas, pasillos, escaleras, entre otros.

Round luminaire for mounting to ceiling or wall.

Housing: polypropylene and UV stabilized.

Diffuser: opal polycarbonate.

Surface finish: white or black. Other colours, on request.

Light distribution: symmetric.

Light source: LED.

Colour rendering index (CRI): CRI>80.

Colour temperature (K): 3000K, 4000K.

Colour tolerance (SDCM): 3 MacAdam's ellipses.

Control gear: On-Off (HF).

On request: radio motion sensor.

Protection degree (IP): IP44.

Mounting: directly to ceiling or wall with screws.

Areas of application: balconies, corridors, stairs and others.



5 Años Garantía
 Years Warranty

Vida Útil / Lifetime
 50.000h
 L80 B20

NO UV
 IR

CRI>80

LED

IP44

IK10

F

CE

MacAdam

SDCM


≤3

HF
 ON/OFF

220-240V
 50-60Hz


W	lm* 3000K	lm* 4000K	CRI	T° Amb	Ø D	H	Kg
9	920	980	>80	-17°C +35°C	300	90	0,60
12	1300	1400	>80	-17°C +35°C	300	90	0,60
16	2000	2150	>80	-17°C +35°C	300	90	0,60

*Flujo luminoso neto a temperatura ambiente ta=25°C. *Output luminous flux at ambient temperature ta=25°C.



Ejemplo para componer una referencia. Example to compose a reference.

Modelo	Potencia	K	CRI	Alimentación	Color
Model	Power	K	CRI	Control gear	Colour
S1 CAM	16W	4000K	CR180	HF	Blanco



La rápida evolución tecnológica del LED modifica de manera continua sus prestaciones.

Los datos aquí facilitados son orientativos.

BIAR Lighting, S.L. se reserva el derecho para realizar ligeras modificaciones técnicas sin previo aviso.

The rapid technological evolution of LED changes continuously its performance.

The data provided here are approximate.

BIAR Lighting, S.L. reserve the right to make slight changes in technical data without previous notice.